

Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-9750-0
 Version number:
 10.00

 Revision date:
 25/09/2013
 Supersedes date:
 14/09/2012

Transportation version number: 1.00 (13/07/2010)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 08984 General Purpose Adhesive Cleaner (EU-7284)

Product identification numbers

FS-9100-3159-0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

General Purpose Adhesive Cleaner.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive Indication of danger

Highly flammable; F; R11 Harmful; Xn; R20/21 Harmful; Xn; R65 Irritant; Xi; R38

Dangerous for the environment; N; R51/53

For full text of R phrases, see Section 16.

2.2. Label elements

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)







Highly Flammable

Dangerous for the environment

Contains:

Naphtha (petroleum), hydrotreated light; Xylene

Risk phrases

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R65 Harmful: May cause lung damage if swallowed.

R51/53 Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety phrases

S16 Keep away from sources of ignition - No Smoking.

S23A Do not breathe vapour.

S36/37 Wear suitable protective clothing and gloves.

S62 If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or

label.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Notes on labelling

Updated per Regulation (EC) 648/2004 on detergents.

Ingredients required per 648/2004 (not required on industrial label): >30%: Aromatic hydrocarbons, aliphatic hydrocarbons. Nota P applied for CAS# 64742-49-0.

N; R51/53 classification applied for CAS# 64742-49-0 based on vendor information.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Xylene	1330-20-7	EINECS 215-	30 - 60	Xn:R20-21; Xi:R38; R10 - Nota
		535-7		C (EU)
				Flam. Liq. 3, H226; Acute Tox.
				4, H332; Acute Tox. 4, H312;
				Skin Irrit. 2, H315 - Nota C
				(CLP)
Naphtha (petroleum), hydrotreated light	64742-49-0	EINECS 265-	30 - 60	Xn:R65 - Nota 4,P (EU)
		151-9		F:R11 (Vendor)
				Xi:R38; R67 (Self Classified)
				Asp. Tox. 1, H304 - Nota P
				(CLP)

Page: 2 of 16

				Flam. Liq. 2, H225; Skin Irrit. 2,
				H315; STOT SE 3, H336 (Self
				Classified)
Ethylbenzene	100-41-4	EINECS 202-	5 - 10	F:R11; Xn:R20 (EU)
		849-4		R52 (Self Classified)
				Flam. Liq. 2, H225; Acute Tox.
				4, H332 (CLP)
Toluene	108-88-3	EINECS 203-	0.1 - 1	Repr.Cat.3:R63; F:R11;
		625-9		Xn:R48/20; Xn:R65; Xi:R38;
				R67 - Nota 4 (EU)
				Flam. Liq. 2, H225; Asp. Tox. 1,
				H304; Skin Irrit. 2, H315; Repr.
				2, H361d; STOT SE 3, H336;
				STOT RE 1, H372 (CLP)

Please see section 16 for the full text of any R phrases and H statements referred to in this section Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning: A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

Page: 4 of 16

8.1 Control parameters

Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	Health and Safety Comm.	TWA:441 mg/m3(100 ppm);STEL:552 mg/m3(125	Skin Notation
		(UK)	ppm)	
Toluene	108-88-3	Health and	TWA: 191 mg/m³ (50 ppm);	Skin Notation
		Safety Comm.	STEL: 384 mg/m ³ (100 ppm)	
		(UK)		
Xylene	1330-20-7	Health and	TWA:220 mg/m3(50	Skin Notation
		Safety Comm.	ppm);STEL:441 mg/m3(100	
		(UK)	ppm)	

Health and Safety Comm. (UK): UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

As a good industrial hygiene practice:

Wear eye/face protection.

The following eye protection(s) are recommended: Safety glasses with side shields. Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Polyvinyl alcohol (PVA). Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Page: 5 of 16

Physical state Liquid.

Appearance/Odour Colourless, transparent, solvent odour.

Odour threshold

pH

No data available.

Not applicable.

Boiling point/boiling range

Melting point

Not applicable.

Flammability (solid, gas)

Explosive properties

Oxidising properties

Not applicable.

Not classified

Not classified

Flash point >= 2 °C [Test Method: Tagliabue closed cup]

Autoignition temperatureNo data available.Flammable Limits(LEL)0.9 % volumeFlammable Limits(UEL)7 % volume

Vapour pressure <=893.3 Pa [@ 20 °C]
Relative density 0.802 [Ref Std:WATER=1]

Water solubility Negligible Solubility- non-water No data available.

Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour density>=3.7 [Ref Std: AIR=1]

Decomposition temperature *No data available.*

Viscosity 0.001 - 0.01 Pa-s [@ 23 °C]

Density 0.802 g/ml

9.2. Other information

Volatile organic compounds (VOC)No data available.Percent volatile100 % volumeVOC less H2O & exempt solventsNo data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance Condition

Page: 6 of 16

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Target Organ Effects:

Single exposure may cause:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

Acute Toxicity

10400 1 Onioloj					
Name	Route	Species	Value		
Overall product	Inhalation-		Data not available or insufficient for classification;		

Page: 7 of 16

	Vapor(4 hr)		calculated ATE48.6 mg/l
Overall product	Ingestion		Data not available or insufficient for classification; calculated ATE >5,000 mg/kg
Naphtha (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Naphtha (petroleum), hydrotreated light	Inhalation-	Rat	LC50 > 14.7 mg/l
	Vapor (4		
	hours)		
Naphtha (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-	Rat	LC50 29 mg/l
•	Vapor (4		
	hours)		
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapor (4		
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		-
	hours)		
Toluene	Ingestion	Rat	LD50 2,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated light	Rabbit	Irritant
Xylene	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Mild irritant
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated light	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant

Skin Sensitisation

Name	Species	Value
Naphtha (petroleum), hydrotreated light	Guinea	Not sensitizing
	pig	
Xylene		Data not available or insufficient for classification
Ethylbenzene	Human	Not sensitizing
Toluene	Guinea	Not sensitizing
	pig	

Respiratory Sensitisation

Name	Species	Value
Naphtha (petroleum), hydrotreated light		Data not available or insufficient for classification
Xylene		Data not available or insufficient for classification
Ethylbenzene		Data not available or insufficient for classification
Toluene		Data not available or insufficient for classification

Germ Cell Mutagenicity

Germ Cen Wutagementy		
Name	Route	Value
Naphtha (petroleum), hydrotreated light	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Naphtha (petroleum), hydrotreated light	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Xylene	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Xylene	Ingestion	Not toxic to male reproduction	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Xylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	premating & during gestation
Toluene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Does not cause effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration

Naphtha (petroleum),	Inhalation	central nervous	May cause drowsiness or		NOAEL Not	
hydrotreated light		system depression	dizziness		available	
Naphtha (petroleum),	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
hydrotreated light			data are not sufficient for		available	
			classification			
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3	8 hours
					mg/l	
Xylene	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness		available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
,		1 ,	data are not sufficient for		available	
			classification			
Xylene	Inhalation	eyes	Some positive data exist, but the	Rat	NOAEL 3.5	not available
,			data are not sufficient for		mg/l	
			classification		8	
Xylene	Inhalation	liver	Some positive data exist, but the	Multiple	NOAEL Not	
,			data are not sufficient for	animal	available	
			classification	species	a variation	
Xylene	Ingestion	central nervous	May cause drowsiness or	Multiple	NOAEL Not	
Trylene	mgestion	system depression	dizziness	animal	available	
		system depression	dizziicss	species	avanabic	
Xylene	Ingestion	eves	Some positive data exist, but the	Rat	NOAEL 250	not applicable
Aylene	ingestion	Cycs	data are not sufficient for	Rat	mg/kg	not applicable
			classification		mg/kg	
Ethylbenzene	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
Ethylochizene	IIIIaiatioii	system depression	dizziness	Human	available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
Ethylbenzene	IIIIaiatioii	respiratory irritation	data are not sufficient for	and	available	
			classification	animal	avanable	
Toluene	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
Totuene	innaiation			Human		
T. 1	7.1.1.0	system depression	dizziness	***	available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for		available	
			classification		370.177	
Toluene	Inhalation	immune system	Some positive data exist, but the	Mouse	NOAEL	3 hours
			data are not sufficient for		0.004 mg/l	
			classification	1		
Toluene	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
		system depression	dizziness	1	available	and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system hematopoietic system muscles kidney and/or bladder respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin	All data are negative	Mouse	NOAEL	103 weeks

Page: 10 of 16

		endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system			1,000 mg/kg/day	
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 105 mg/kg/day	28 days

Page: 11 of 16

Toluene	Ingestion	immune system	Some positive data exist, but the	Mouse	NOAEL 105	4 weeks
		-	data are not sufficient for		mg/kg/day	
			classification			

Aspiration Hazard

Name	Value
Naphtha (petroleum), hydrotreated light	Aspiration hazard
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Ethylbenzene	100-41-4	Green Algae	Experimental	96 hours	EC50	3.6 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	24 hours	EC50	1.81 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Sheepshead Minnow	Experimental	28 days	NOEC	3.2 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Xylene	1330-20-7		Data not available or insufficient for classification			
Naphtha (petroleum), hydrotreated light	64742-49-0		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethylbenzene	100-41-4	Experimental		Photolytic half-	4.26 days (t	Other methods
		Photolysis		life (in air)	1/2)	
Ethylbenzene	100-41-4	Laboratory	14 days	BOD	81 % weight	Other methods
		Biodegradation				
Toluene	108-88-3	Experimental		Photolytic half-	5.38 days (t	Other methods
		Photolysis		life (in air)	1/2)	
Toluene	108-88-3	Experimental	14 days	BOD	100 % weight	OECD 301C - MITI
		Biodegradation	-			test (I)
Xylene	1330-20-7	Data not	N/A	N/A	N/A	N/A

Page: 12 of 16

		available or				
		insufficient for				
		classification				
Naphtha	64742-49-0	Data not	N/A	N/A	N/A	N/A
(petroleum),		available or				
hydrotreated		insufficient for				
light		classification				

12.3: Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethylbenzene	100-41-4	Experimental BCF - Other		Bioaccumulati on factor	15	Other methods
Toluene	108-88-3	Experimental Bioconcentrati on		Log Kow	2.73	Other methods
Xylene	1330-20-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated light	64742-49-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

070604* Other organic solvents, washing liquids and mother liquors

20 01 13* Solvents

SECTION 14: Transportation information

FS-9100-3159-0

ADR/RID: UN1993, FLAMMABLE LIQUID, N.O.S., LIMITED QUANTITY, (XYLENE), 3., II, (E), ADR Classification Code: F1.

IMDG-CODE: UN1993, FLAMMABLE LIQUID N.O.S., (XYLENE), 3, II, LIMITED QUANTITY, Marine Pollutant,

(HYDROTREATED LIGHT NAPHTHA (PETROLEUM)), EMS: FE,SE.

ICAO/IATA: UN1993, FLAMMABLE LIQUID, N.O.S., (XYLENE), 3., II, LIMITED QUANTITY.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer
Toluene	108-88-3	Gr. 3: Not classifiable	International Agency
			for Research on Cancer
Xylene	1330-20-7	Gr. 3: Not classifiable	International Agency
			for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

List of relevant R-phrases

R10 Flammable. R11 Highly flammable. R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R21 Harmful in contact with skin.

R38 Irritating to skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53 Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

R52 Harmful to aquatic organisms.

R63 Possible risk of harm to the unborn child.
 R65 Harmful: May cause lung damage if swallowed.
 R67 Vapours may cause drowsiness and dizziness.

Revision information:

Revision Changes:

Section 16: List of relevant R phrase information information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

 $Section \ 12: Bioccumulative \ potential \ information \ information \ was \ modified.$

Section 9: Flammability (solid, gas) information information was modified.

Section 16: Regulations - Inventories - EU ONLY information was modified.

Copyright information was modified.

Section 11: Acute Toxicity table information was modified.

Carcinogenicity Table information was modified.

Serious Eye Damage/Irritation Table information was modified.

Germ Cell Mutagenicity Table information was modified.

Skin Sensitisation Table information was modified.

Respiratory Sensitisation Table information was modified.

Lactation Table information was modified.

Reproductive Toxicity Table information was modified.

Skin Corrosion/Irritation Table information was modified.

Target Organs - Repeated Table information was modified.

Target Organs - Single Table information was modified.

Section 11: Health Effects - Skin information information was modified.

Section 11: Health Effects - Inhalation information information was modified.

Section 11: Health Effects - Ingestion information information was modified.

 $Section \ 5: Fire \ - \ Extinguishing \ media \ information \ information \ was \ modified.$

Section 6: Accidental release clean-up information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Personal Protection - Eye information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 8: Skin protection - protective clothing text information was added.

Label: Graphic Text information was added.

Label: Graphic Text information was added.

Section 9: Odour Threshold information was added.

Section 9: Solubility (non-water) information was added.

Section 09: Decomposition Temperature information was added.

Section 11: Single exposure may cause: heading information was added.

Section 11: Prolonged or repeated exposure may cause: heading information was added.

Section 11: Single exposure may cause standard phrases information was added.

Section 11: Prolonged or repeated exposure may cause standard phrases information was added.

Section 10: Hazardous decomposition products during combustion text information was added.

Label: Graphic information was added.

Label: Graphic information was added.

Label: Graphic Text information was added.

Section 9: Flammability (solid, gas) information information was added.

Section 2: Symbol information was deleted.

Section 2: Symbols heading information was deleted.

Section 12: Acute aquatic hazard information information was deleted.

Section 12: Chronic aquatic hazard heading information was deleted.

Section 12: Acute aquatic hazard heading information was deleted.

Section 12: Chronic aquatic hazard information information was deleted.

Section 8: mg/m³ key information was deleted.

Section 8: ppm key information was deleted.

Section 15: Ingredient information per Regulation EC No. 648/2004 information was deleted.

Section 11: Health Effects - Other information information was deleted.

Section 8: Personal Protection - Skin/hand information information was deleted.

Section 8: Personal Protection - Respiratory Information information was deleted.

Section 15: Ingredient information per Regulation EC No. 648/2004 heading information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk