

(GB)

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 22.04.2015 / 0006
Replaces revision of / Version: 28.04.2014 / 0005
Valid from: 22.04.2015
PDF print date: 24.04.2015
Speed Tec 250 mL
Art.: 3720

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Speed Tec 250 mL
Art.: 3720

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Fuel additive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
STOT RE	1	H372-Causes damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Dangerous for the environment, R52/53

Xn, Harmful, R65

R66

Xn, Harmful, R48/20

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects. H372-Causes damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P260-Do not breathe vapours or spray.

P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. P314-Get medical advice/attention if you feel unwell.

P405-Store locked up.

P501-Dispose of contents/container to special waste collection point.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C10, aromatics, <1% naphthalene

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119473977-17-XXXX
Index	---
EINECS, ELINCS, NLP	919-164-8 (REACH-IT-List-Nr.)
CAS	CAS ---
content %	70-80
Classification according to Directive 67/548/EEC	Harmful, Xn, R48/20 Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 Aquatic Chronic 3, H412 STOT RE 1, H372 (central nervous system) (as inhalation)
Hydrocarbons, C10, aromatics, <1% naphthalene	
Registration number (REACH)	01-2119463583-34-XXXX
Index	---

(GB)

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

EINECS, ELINCS, NLP	918-811-1 (REACH-IT List-No.)
CAS	(64742-94-5)
content %	2,5-5
Classification according to Directive 67/548/EEC	Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	---
EINECS, ELINCS, NLP	926-141-6 (REACH-IT List-No.)
CAS	CAS ---
content %	1-5
Classification according to Directive 67/548/EEC	Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119458869-15-XXXX
Index	---
EINECS, ELINCS, NLP	925-653-7 (REACH-IT List-No.)
CAS	(64742-81-0)
content %	1-5
Classification according to Directive 67/548/EEC	Dangerous for the environment, R52 Dangerous for the environment, R53 Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	920-360-0 (REACH-IT List-No.)
CAS	---
content %	1-5
Classification according to Directive 67/548/EEC	Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 22.04.2015 / 0006

Replaces revision of / Version: 28.04.2014 / 0005

Valid from: 22.04.2015

PDF print date: 24.04.2015

Speed Tec 250 mL

Art.: 3720

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Product removes fat.

Dermatitis (skin inflammation)

Ingestion:

Oedema of the lungs

Lung damage

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher

Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Hydrocarbons

Toxic pyrolysis products.

Explosive vapour/air mixture

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Solvent resistant floor
 Do not store with oxidizing agents.
 Store in a well ventilated place.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m³

(GB)	Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:70-80
	WEL-TWA:	1000 mg/m ³	WEL-STEL: ---
	BMGV:	---	Other information: (WEL acc. to RCP-method, EH40)
(GB)	Chemical Name	Hydrocarbons, C10, aromatics, <1% naphthalene	Content %:2,5-5
	WEL-TWA:	500 mg/m ³ (Aromatics)	WEL-STEL: ---
	BMGV:	---	Other information: ---
(GB)	Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Content %:1-5
	WEL-TWA:	1200 mg/m ³ (>=C7 normal and branched chain alkanes)	WEL-STEL: 2(II) (AGW)
	BMGV:	---	Other information: ---
(GB)	Chemical Name	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:1-5
	WEL-TWA:	800 mg/m ³	WEL-STEL: ---
	BMGV:	---	Other information: (WEL acc. to RCP-method, EH40)
(GB)	Chemical Name	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)	Content %:1-5
	WEL-TWA:	800 mg/m ³	WEL-STEL: ---

GB

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)
-----------	---

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Industrial / commercial	Human - dermal	Long term, systemic effects	DNEL	44	mg/kg bw/day	
Industrial / commercial	Human - inhalation	Long term, systemic effects	DNEL	330	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	71	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	44	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	330	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	71	mg/m3	

Hydrocarbons, C10, aromatics, <1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - dermal	Long term	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term	DNEL	151	mg/m3	
Consumer	Human - dermal	Long term	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term	DNEL	32	mg/m3	
Consumer	Human - oral	Long term	DNEL	7,5	mg/kg bw/day	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374)

Protective gloves made of polyvinyl alcohol (EN 374)

Protective Viton® / fluoroelastomer gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	63 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% (Naphtha (petroleum), hydrodesulfurized heavy)

Page 8 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Upper explosive limit:	7 Vol-% (Naphtha (petroleum), hydrodesulfurized heavy)
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,82 g/ml (15°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm ² /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Speed Tec 250 mL

Art.: 3720

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	t					n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

GB

Page 9 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Other information:						Classification according to calculation procedure.
--------------------	--	--	--	--	--	--

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3400	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	13,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Maximum achievable concentration.
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						Analogous conclusion, Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): central nervous system
Aspiration hazard:						Yes
Symptoms:						headaches, dizziness, fatigue, nausea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:						Target organ(s): central nervous system

Hydrocarbons, C10, aromatics, <1% naphthalene						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative

GB

Page 10 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Aspiration hazard:						Yes
Symptoms:						drowsiness, headaches, drowsiness, dizziness

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising (Analogous conclusion)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Analogous conclusion, Negative
Germ cell mutagenicity:					in vivo	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion, Not to be expected
Aspiration hazard:						Harmful: may cause lung damage if swallowed.
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5060	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	~3400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>13,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	13,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising

(GB)

Page 11 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEC	>=300	ppm	Rat	OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Aspiration hazard:						Yes
Symptoms:						Oedema of the lungs, Chemical pneumonitis (condition similar to pneumonia), drowsiness, unconsciousness, headaches, dizziness, drying of the skin., Gastrointestinal disturbances, Irritation of the mouth and throat

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Speed Tec 250 mL Art.: 3720							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							Isolate as much as possible with an oil separator.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>10- <100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	NOEC/NOEL	21d	0,097	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to daphnia:	EL50	48h	10-22	mg/l	Daphnia magna		Analogous conclusion
Toxicity to algae:	EL50	72h	10-100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

GB

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Persistence and degradability:		28d	74,7	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:	Log Pow		4,2-7,2				
Bioaccumulative potential:	Log Kow		4,2-7,2				A notable biological accumulation potential has to be expected (LogPow > 3).
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>10-100	mg/l			

Hydrocarbons, C10, aromatics, <1% naphthalene

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	2 -5	mg/l			
Toxicity to fish:	LL50	96h	2 - 5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48h	3 -10	mg/l			
Toxicity to daphnia:	EL50	48h	3 -10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	EC50	72h	1 -3	mg/l			
Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	49,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
Water solubility:							Insoluble

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR	
Toxicity to daphnia:	EL50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR	
Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

GB

Page 13 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:	Log Pow		6-8				
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	10-100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to fish:	LL50	96h	10-30	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	48h	10-22	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	EL50	48h	10-22	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	EC50	72h	4,6-10	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to algae:	NOELR	72h	1	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	74,7	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:							To be expected
Mobility in soil:							n.a.
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other adverse effects:							Product floats on the water surface.
Other information:							Isolate as much as possible with an oil separator.
Water solubility:							Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be
 allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
 07 07 04 other organic solvents, washing liquids and mother liquors
 14 06 03 other solvents and solvent mixes

Recommendation:

Pay attention to local and national official regulations
 Implement substance recycling.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations
 Empty container completely.
 Untampered packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name: n.a.
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Classification code: n.a.
 LQ (ADR 2015): n.a.
 LQ (ADR 2009): n.a.
 Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Marine Pollutant: n.a.
 Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:
 Transport hazard class(es): n.a.
 Packing group: n.a.
 Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.
 Observe youth employment law (German regulation).
 Observe law on protection of expectant mothers (German regulation).
 Directive 2010/75/EU (VOC): ~ 90,3 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

SECTION 16: Other information

These details refer to the product as it is delivered.
 Revised sections:

2, 3, 8, 16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
STOT RE 1, H372	Classification according to calculation procedure.

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 51 Toxic to aquatic organisms.
 52 Harmful to aquatic organisms.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 53 May cause long-term adverse effects in the aquatic environment.
 65 Harmful: may cause lung damage if swallowed.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.
 H372 Causes damage to organs through prolonged or repeated exposure by inhalation.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 STOT RE — Specific target organ toxicity - repeated exposure
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service

Page 16 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 22.04.2015 / 0006
 Replaces revision of / Version: 28.04.2014 / 0005
 Valid from: 22.04.2015
 PDF print date: 24.04.2015
 Speed Tec 250 mL
 Art.: 3720

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development

Page 17 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 22.04.2015 / 0006
Replaces revision of / Version: 28.04.2014 / 0005
Valid from: 22.04.2015
PDF print date: 24.04.2015
Speed Tec 250 mL
Art.: 3720

org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.