

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 19.01.2011 / 0005
Replaces revision of / Version: 24.04.2009 / 0004
Valid from: 19.01.2011
PDF print date: 19.02.2011
Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Bremsen-Anti-Quietsch-Spray 400ml
Art.: 3079

1.2 Relevant identified uses of the substance or mixture:

Lubricant
Sector of use [SU]:
SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 - Consumer uses: Private households (=general public = consumers)
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC24 - Lubricants, greases, release products
Process category [PROC]:
PROC 7 - Industrial spraying
PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC10 - Roller application or brushing
PROC11 - Non industrial spraying
Environmental Release Category [ERC]:
ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles
ERC 7 - Industrial use of substances in closed systems
ERC 8a - Wide dispersive indoor use of processing aids in open systems
ERC 8d - Wide dispersive outdoor use of processing aids in open systems
Article Categories [AC]:
AC99 - Not required.

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr
Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone

Advisory office in case of poisoning:

Tel.:

Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments).

F+, Extremely flammable

Page 2 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

R67
 Xi, Irritant, R38
 Dangerous for the environment, R52-53

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments).



Symbols: F+/Xi

Indications of danger:

Extremely flammable

Irritant

R-phrases:

38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

S-phrases:

23 Do not breathe vapour/spray.

35 This material and its container must be disposed of in a safe way.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

Additions:

Pressurized container:

protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture contains no vPvB substance (vPvB = very persistent, very bioaccumulative).

The mixture contains no PBT substance (PBT = persistent, bioaccumulative, toxic).

Danger of bursting (explosion) when heated

When using: development of explosive vapour/air mixture possible.

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

Naphtha (petroleum), hydrotreated light	
Registration number (ECHA)	-
Index	649-328-00-1
EINECS, ELINCS	265-151-9
CAS	CAS 64742-49-0
content %	20-<25
Symbol	F/Xn/Xi/N
R-phrases	11-38-51-53-65-67
Classification categories / Indications of danger	Dangerous for the environment, Harmful, Highly flammable, Irritant
Hazard class/Hazard category	Hazard statement

Page 3 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Flam. Liq./2	H225
Skin Irrit./2	H315
Aquatic Chronic/2	H411
Asp. Tox./1	H304
STOT SE/3	H336

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.
 Keep Data Sheet available.

Ingestion

Call doctor immediately - have Data Sheet available.
 Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Where relevant delayed occurring symptoms and effects will be found in section 11. or at the exposure routes under section 4.1.

The following may occur:

Irritation of the eyes
 Irritation of the respiratory tract
 Coughing
 Headaches
 Nausea
 Effects/damages the central nervous system
 Narcotic effect.
 With long-term contact:
 Dermatitis (skin inflammation)
 Drying of the skin.
 Irritation of the skin.

Other dangerous properties cannot be ruled out.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
 Extinguisher powder
 Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
 Hydrocarbons
 Toxic pyrolysis products.
 Danger of explosion by prolonged heating.
 Explosive vapour/air mixture

In case of spreading near the ground, flashback to distance sources of ignition is possible.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

5.3 Advice for firefighters

Protective respirator with independent air supply.
 According to size of fire
 Full protection, if necessary
 Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.
 Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
 Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
 Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.
 Only from a specialist.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

Ensure good ventilation.
 Keep away from sources of ignition - Do not smoke.
 Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Do not use the product in enclosed spaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.
 General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with oxidizing agents.
 Observe special regulations for aerosols!
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

WEL-TWA: 700 mg/m3 (AGW)	WEL-STEL: 4(II) (AGW)	---
BMGV: ---	Other information: ---	

Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
BMGV: ---	Other information: ---	

Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
BMGV: ---	Other information: ---	

Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:	Tight fitting protective goggles with side protection (EN 166).
Skin protection - Hand protection:	Protective nitrile gloves (EN 374)
Minimum layer thickness in mm:	
0,4	
Protective Viton gloves (EN 374)	
Protective gloves made of polyvinyl alcohol (EN 374)	
Minimum layer thickness in mm:	
0,7	
Permeation time (penetration time) in minutes:	
> 480 (Level 6)	
Skin protection - Other:	Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)
Boots (EN ISO 20347)	
PVC	
Respiratory protection:	Normally not necessary.
If OES or MEL is exceeded.	
Gas mask filter A (EN 14387), code colour brown	
At high concentrations:	
Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)	

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Page 6 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol
Physical state:	Substance: Liquid
Colour:	Blue
Colour:	Light
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	-60 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	1,4 Vol-%
Upper explosive limit:	32 Vol-%
Vapour pressure:	4300 hPa
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,63 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	510 °C (Ignition temperature)
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.4 to 10.6.

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.4 to 10.6.

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.4 to 10.6.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Page 7 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.4 to 10.6.

See also section 5.3

SECTION 11: Toxicological information

Classification according to calculation procedure.

Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	t			---		n.d.a.
Acute toxicity, by dermal route:				---		n.d.a.
Acute toxicity, by inhalation:				---		n.d.a.
Skin corrosion/irritation:				---		n.d.a.
Serious eye damage/irritation:				---		n.d.a.
Respiratory or skin sensitisation:				---		n.d.a.
Germ cell mutagenicity:				---		n.d.a.
Carcinogenicity:				---		n.d.a.
Reproductive toxicity:				---		n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):				---		n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):				---		n.d.a.
Aspiration hazard:				---		n.d.a.
Respiratory tract irritation:				---		n.d.a.
Repeated dose toxicity:				---		n.d.a.
Symptoms:				---		n.d.a.

Naphtha (petroleum), hydrotreated light						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:				---		Irritant
Serious eye damage/irritation:				---		Not irritant
Respiratory or skin sensitisation:				---		Not sensitising
Germ cell mutagenicity:				---		Negative
Carcinogenicity:				---		n.d.a.
Reproductive toxicity:				---		n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):				---		n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):				---		n.d.a.
Aspiration hazard:				---		n.d.a.
Respiratory tract irritation:				---		n.d.a.
Repeated dose toxicity:				---		n.d.a.
Symptoms:				---		dizziness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Teratogenicity:				---		Negative

Butane

Page 8 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Toxicity/effect	Endpoint t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:				---		n.d.a.
Acute toxicity, by dermal route:				---		n.d.a.
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Skin corrosion/irritation:				---		n.d.a.
Serious eye damage/irritation:				---		n.d.a.
Respiratory or skin sensitisation:				---		n.d.a.
Germ cell mutagenicity:				---	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				---		n.d.a.
Reproductive toxicity:				---		n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):				---		n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):				---		n.d.a.
Aspiration hazard:				---		n.d.a.
Respiratory tract irritation:				---		n.d.a.
Repeated dose toxicity:				---		n.d.a.
Symptoms:				---		ataxia, breathing difficulties, dizziness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity/effect	Endpoint t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:				---		n.d.a.
Acute toxicity, by dermal route:				---		n.d.a.
Acute toxicity, by inhalation:				---		n.d.a.
Skin corrosion/irritation:				---		n.d.a.
Serious eye damage/irritation:				---		n.d.a.
Respiratory or skin sensitisation:				---		n.d.a.
Germ cell mutagenicity:				---		n.d.a.
Germ cell mutagenicity (bacterial):				---	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:				---		n.d.a.
Reproductive toxicity:				---		n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):				---		n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):				---		n.d.a.
Aspiration hazard:				---		n.d.a.
Respiratory tract irritation:				---		n.d.a.
Repeated dose toxicity:				---		n.d.a.
Symptoms:				---		breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane						
Toxicity/effect	Endpoint t	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:				---		n.d.a.
Acute toxicity, by dermal route:				---		n.d.a.

Page 10 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

Propane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

Isobutane							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							n.d.a.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

16 05 04 gases in pressure containers (including halons) containing dangerous substances

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

General statements

UN number:

1950

Transport by road/by rail (ADR/RID)

UN proper shipping name:

UN 1950 AEROSOLS



GB

Page 11 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 19.01.2011 / 0005
 Replaces revision of / Version: 24.04.2009 / 0004
 Valid from: 19.01.2011
 PDF print date: 19.02.2011
 Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Transport hazard class(es):	2.1
Packing group:	-
Classification code:	5F
LQ (ADR 2011):	1 L
LQ (ADR 2009):	2
Environmental hazards:	Not applicable
Tunnel restriction code:	D

Transport by sea (IMDG-code)

UN proper shipping name:		
AEROSOLS		
Transport hazard class(es):	2.1	
Packing group:	-	
EmS:	F-D, S-U	
Marine Pollutant:	n.a.	
Environmental hazards:	Not applicable	

Transport by air (IATA)

UN proper shipping name:		
Aerosols, flammable		
Transport hazard class(es):	2.1	
Packing group:	-	
Environmental hazards:	Not applicable	

Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Additional information:

Danger code and packing code on request.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: Yes

Observe incident regulations.

Observe youth employment law (German regulation).

Regulation (EC) No 1907/2006, Annex XVII.

VOC 1999/13/EC 82,2% w/w

15.2 Chemical safety assessment

No information available at present.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: n.a.

The following statements are the indicated R-phrases / H-phrases and classification codes (GHS/CLP) for the ingredients (listed in Section 3).

11 Highly flammable.

38 Irritating to skin.

51 Toxic to aquatic organisms.

52 Harmful to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq.-Flammable liquid

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 19.01.2011 / 0005

Replaces revision of / Version: 24.04.2009 / 0004

Valid from: 19.01.2011

PDF print date: 19.02.2011

Bremsen-Anti-Quietsch-Spray 400ml Art.: 3079

Skin Irrit.-Skin irritation

Aquatic Chronic-Hazardous to the aquatic environment - chronic

Asp. Tox.-Aspiration hazard

STOT SE-Specific target organ toxicity - single exposure - narcotic effects

Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

VOC = Volatile organic compounds

AOX = Adsorbable organic halogen compounds

ATE = Acute Toxicity Estimates according to Regulation (EC) 1272/2008 (CLP)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.