

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifiers**

Article No. (manufacturer/supplier) 346  
Identification of the substance or mixture FEYCOFIX 346 KH-Decklack  
gültig für alle Farbtöne  
seidenglänzend

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses:**

Single pack paint, based on synthetic resin, for general use in industrial applications by spraying, brushing, rolling or dipping

**1.3. Details to the supplier providing the material safety data sheet****Producer:****FEYCOLOR GmbH**

Maxhuettenstraße 6,  
93055 Regensburg,  
Germany

Tel.: +49 (0) 941/ 60497-0  
Fax.: +49 (0) 941/ 60497-30  
info@feycolor.com

[www.feycolor.com](http://www.feycolor.com)

Office hours:  
Monday - Thursday: 08:00 - 12:00 and 13:00 - 16:00  
Friday: 08:00 - 12:00

Email: sd@feycolor.com  
[www.feycolor.com](http://www.feycolor.com) <<http://www.feycolor.com>>

**1.4. Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)****SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

**Classification according to Directive 67/548/EEC or 1999/45/EC**

This mixture is classified as hazardous according to 1999/45/EC.

R10		Flammable
Xn; R20/21	Harmful	Harmful by inhalation and in contact with skin.
Xi; R38	Irritant	Irritating to skin.
R52-53		Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]****Hazard pictograms****Warning****Hazard statements**

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical equipment.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container to industrial incineration plant.

**contains:**

n.a.

**Supplemental Hazard information (EU)**

EUH208 Contains 2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate; 2-butanone oxime. May produce an allergic reaction.

**Labelling (67/548/EEC or 1999/45/EC)**



Xn Harmful

**Hazard statements**

- 10 Flammable
- 20/21 Harmful by inhalation and in contact with skin.
- 38 Irritating to skin.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Precautionary statements**

- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 36/37 Wear suitable protective clothing and gloves.
- 38 In case of insufficient ventilation, wear suitable respiratory equipment.
- 51 Use only in well-ventilated areas.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheet.
- 23 Do not breathe vapour.

**contains:**

xylene, mixture of isomers

**Special provisions concerning the labelling of certain mixtures**

99 Contains 2-butanone oxime; 2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester polymer with butyl 2-propenoate. May produce an allergic reaction.

2.3. Other hazards

**SECTION 3: Composition / information on ingredients**

3.2. Mixtures

**Product description / chemical characterization**

**Description** Gemisch aus nachfolgend angeführten Stoffen mit ungefährlichen Beimengungen

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
215-535-7 1330-20-7 601-022-00-9	02-2119488216-32 xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315	12,5 - 20
203-603-9 108-65-6 607-195-00-7	01-2119475791-29 2-methoxy-1-methylethyl acetate Flam. Liq. 3 H226	2,5 - 5
215-535-7 1330-20-7	01-2119488216-32 xylene Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2	2,5 - 5

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 346 FEYCOFIX 346 KH-Decklack  
Print date: 29.05.2015 Revision date: 01.05.2015  
Version: 2.0 Issue date: 01.05.2015

999998 EN  
Page 3 / 10

	H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	
265-185-4 64742-82-1	01-2119458049-33 Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	1 - 2,5
918-668-5 64742-95-6	01-2119455851-35 Solvent naphtha (petroleum), light arom. Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	1 - 2,5
201-148-0 78-83-1 603-108-00-1	01-2119484609-23 2-methylpropan-1-ol Flam. Liq. 3 H226 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	1 - 2,5
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	1 - 2,5
203-539-1 107-98-2 603-064-00-3	01-2119457435-35 1-methoxy-2-propanol Flam. Liq. 3 H226 / STOT SE 3 H336	1 - 2,5
221-108-6 3006-13-1	dodecylethyldimethylammonium ethyl sulphate Acute Tox. 4 H302 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Aquatic Acute 1 H400	< 0,5
1259547-09-5	2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate Skin Sens. 1 H317	< 0,5
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	< 0,5

## Classification according to Directive 67/548/EEC or 1999/45/EC

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
215-535-7 1330-20-7 601-022-00-9	02-2119488216-32 xylene, mixture of isomers R10 / Xn; R20/21 / Xi; R38	12,5 - 20
203-603-9 108-65-6 607-195-00-7	01-2119475791-29 2-methoxy-1-methylethyl acetate R10	2,5 - 5 *
215-535-7 1330-20-7	01-2119488216-32 xylene, mixture of isomers R10 / Xn; R20/21-48/20-65 / Xi; R36/37/38	2,5 - 5
265-185-4 64742-82-1	01-2119458049-33 Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha R10 / N; R51-53 / Xn; R65 / R66 / R67	1 - 2,5
918-668-5 64742-95-6	01-2119455851-35 Lösungsmittel, C9 Kohlenwasserstoffe, Aromaten R10 / Xi; R37 / N; R51-53 / Xn; R65 / R66 / R67	1 - 2,5
201-148-0 78-83-1 603-108-00-1	01-2119484609-23 2-methylpropan-1-ol R10 / Xi; R37/38-41 / R67	1 - 2,5
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate R10 / R66 / R67	1 - 2,5
203-539-1 107-98-2 603-064-00-3	01-2119457435-35 1-methoxy-2-propanol R10 / R67	1 - 2,5

221-108-6 3006-13-1	Dodecylethyltrimethylammoniummethylsulfat Xn; R22 / C; R34 / N; R50	< 0,5
1259547-09-5	2-Propenoic acid,2-methyl-,2-(dimethylamino)ethyl ester polymer with butyl 2-propenoate R43	< 0,5
202-496-6 96-29-7	01-2119539477-28 2-butanone oxime Carc.Cat.3; R40 / Xn; R21 / Xi; R41 / R43	< 0,5

**Additional information**

\* Substance with a common (EC) occupational exposure limit value.

Full text of R-phrases: see section 16.

Full text of H-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media:**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Extinguishing media which must not be used for safety reasons:**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Special protective equipment for firefighters:**

Provide a conveniently located respiratory protective device.

**Additional information**

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see chapter 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Precautions against fire and explosion:**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values:**

xylene, mixture of isomers

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m<sup>3</sup>; 50 ppm

WEL, STEL: 441 mg/m<sup>3</sup>; 100 ppm

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

1-methoxy-2-propanol

INDEX No. 603-064-00-3 / EC No. 203-539-1 / CAS No. 107-98-2

WEL, TWA: 375 mg/m<sup>3</sup>; 100 ppm

WEL, STEL: 560 mg/m<sup>3</sup>; 150 ppm

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m<sup>3</sup>; 150 ppm

MEL/OES, STEL: 966 mg/m<sup>3</sup>; 200 ppm

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

WEL, TWA: 274 mg/m<sup>3</sup>; 50 ppm

WEL, STEL: 548 mg/m<sup>3</sup>; 100 ppm

2-methylpropan-1-ol

INDEX No. 603-108-00-1 / EC No. 201-148-0 / CAS No. 78-83-1

WEL, TWA: 154 mg/m<sup>3</sup>; 50 ppm  
 WEL, STEL: 231 mg/m<sup>3</sup>; 75 ppm

**Additional information**

TWA : long-term occupational exposure limit value  
 STEL : short-term occupational exposure limit value  
 Ceiling : peak limitation

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: solventresistant Latex gloves  
 Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
 Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
 Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance:**

**Physical state** liquid  
**Colour** see productname  
**Odour** typical

Safety relevant basis data	Unit	Method	Remark
Flash point:	24 °C		
Ignition temperature in °C:	235 °C		
Lower explosion limit:	1,1 Vol-%		
Upper explosion limit:	15,0 Vol-%		
Vapour pressure at 20 °C:	2,72 mbar		
Density at 20 °C:	1,40 g/cm <sup>3</sup>		
Water solubility (g/L):	insoluble		
pH at 20 °C:	n.a. Wt %		
Viscosity at 20 °C:	> 100 s 4 mm	DIN 53211	
Solvent separation test (%):	< 3 %	ADR/RID	
Solid content (%):	69 Wt %		
solvent content:			
Organic solvents:	31,35 Wt %		
Water:	0,00 Wt %		

**9.2. Other information**

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

**10.2. Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.



Article No.: 346  
Print date: 29.05.2015  
Version: 2.0FEYCOFIX 346 KH-Decklack  
Revision date: 01.05.2015  
Issue date: 01.05.2015999998 EN  
Page 7 / 10**10.3. Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4. Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

**10.5. Incompatible materials****10.6. Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

No data on preparation itself available.

**11.1. Information on toxicological effects****Acute toxicity**

2-methoxy-1-methylethyl acetate

oral, LD50, Rat:

n-butyl acetate

oral, LD50, Rat:

Naphtha (petroleum), hydrodesulfurized heavy

oral, LD50, Rat:

**Irritant and corrosive effects**

Toxicological data are not available.

**Sensitisation**

2-methoxy-1-methylethyl acetate

Skin:

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Toxicological data are not available.

**Specific target organ toxicity**

Naphtha (petroleum), hydrodesulfurized heavy

Specific target organ toxicity (single exposure), drowsiness:

**Aspiration hazard**

Toxicological data are not available.

**Practical experience/human evidence**

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

**SECTION 12: Ecological information****overall evaluation**

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

**12.1. Toxicity**

No information available.

**Long-term Ecotoxicity**

Toxicological data are not available.

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**Bioconcentration factor (BCF)**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111 waste paint and varnish containing organic solvents or other dangerous substances

**packaging**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Paint  
 Sea transport (IMDG): PAINT  
 Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

Land transport (ADR/RID): "No good according class 3"  
 containers > 450 l = class 3  
 Sea transport (IMDG)  
 for packages < 30 litres: 3  
 Transport in accordance with 2.3.2.5 of the IMDG Code.  
 Air transport (ICAO-TI / IATA-DGR) 3

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID) n.a.  
 Marine pollutant n.a.

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
 Advices on safe handling: see parts 6 - 8

**Additional information**

**Land transport (ADR/RID)**

tunnel restriction code D/E  
 SONDERVORSCHRIFT 640E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 438

VOC-value (in g/L) ASTM D 2369: 438

##### according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. A/i)): 600 g/l (2007)/500 g/l (2010).

This product contains max 477 g/l VOC.

#### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

##### Other regulations, restrictions and prohibition regulations

### 15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
215-535-7 1330-20-7	xylene, mixture of isomers	02-2119488216-32
202-496-6 96-29-7	2-butanone oxime	01-2119539477-28
203-539-1 107-98-2	1-methoxy-2-propanol	01-2119457435-35
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	01-2119475791-29
201-148-0 78-83-1	2-methylpropan-1-ol	01-2119484609-23
918-668-5 64742-95-6	Lösungsmittel, C9 Kohlenwasserstoffe, Aromaten	01-2119455851-35
215-535-7 1330-20-7	xylene, mixture of isomers	01-2119488216-32
265-185-4 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha	01-2119458049-33

## SECTION 16: Other information

### Relevant R-and H-phrases (Number and full text):

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT RE 2 / H373	Specific target organ toxicity (repeated exposure)	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Corr. 1B / H314	skin corrosion/irritation	Causes severe skin burns and eye damage.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**

Article No.:	346	FEYCOFIX 346 KH-Decklack	
Print date:	29.05.2015	Revision date: 01.05.2015	999998 EN
Version:	2.0	Issue date: 01.05.2015	Page 10 / 10

Aquatic Acute 1 / H400 Skin Sens. 1 / H317 Carc. 2 / H351	Hazardous to the aquatic environment respiratory or skin sensitisation Carcinogenicity	Very toxic to aquatic life. May cause an allergic skin reaction. Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). Flammable
R10 Xn; R20/21 Xi; R38 Carc.Cat.3; R40 Xn; R21 Xi; R41 R43 R67 R66	Harmful Irritant Carcinogenic Cat. 3 (Carc. Cat. 3) Harmful Irritant	Harmful by inhalation and in contact with skin. Irritating to skin. Limited evidence of a carcinogenic effect. Harmful in contact with skin. Risk of serious damage to eyes. May cause sensitization by skin contact. Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.
Xi; R37/38-41	Irritant	Irritating to respiratory system and skin. Risk of serious damage to eyes. Harmful: may cause lung damage if swallowed.
Xn; R22 C; R34 N; R50 Xi; R37 N; R51-53	Harmful Corrosive Dangerous for the environment Irritant Dangerous for the environment	Harmful if swallowed. Causes burns. Very toxic to aquatic life. Irritating to respiratory system. Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Xn; R65 Xn; R20/21-48/20-65	Harmful Harmful	Harmful: may cause lung damage if swallowed. Harmful: may cause lung damage if swallowed. Harmful by inhalation and in contact with skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: may cause lung damage if swallowed.
Xi; R36/37/38	Irritant	Irritating to eyes, respiratory system and skin.

**Additional information**

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.