

Johannes J. Matthies GmbH & Co. KG

Safety Data Sheet

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC JM Uni coolant, ready to use

UFI:

U9DG-48QK-UG0Q-7WHW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Antifreeze agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Street:	Johannes J. Matthies GmbH & Co. KG Hammerbrookstr. 97
Place:	D-20097 Hamburg
	0
Telephone:	+ 49 (0) 40 2 37 21-0
e-mail:	info@matthies.de
Internet:	www.matthies.de
Supplier	
Company name:	Larsson UK Ltd.
Street:	7 Alpha Court, Phoenix Parkway
Place:	GB-NN17 5DP Corby
Telephone:	+ 44 1536 265633
e-mail:	info@larsson.uk.com
Internet:	www.larsson.uk.com
1.4. Emergency telephone	+ 44 1536 265633
<u>number:</u>	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Acute Tox. 4; H302 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling ethanediol, ethylene glycol Signal word: Warning

Pictograms:



Hazard statements H302

Harmful if swallowed.

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Page 2 of 9

H373	May cause damage to kidneys through prolonged or repeated exposure if swallowed.
Precautionary stat	tements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P330	Rinse mouth.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
107-21-1	ethanediol, ethylene glycol				
	203-473-3	603-027-00-1			
	Acute Tox. 4, STOT RE 2; H302 H3	373			
12045-78-2	potassium tetraborate	_		0,125 - 0,25 %	
	215-575-5				
	Repr. 2; H361d				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	imits, M-factors and ATE	
107-21-1	203-473-3	ethanediol, ethylene glycol	45 - 47,5 %
dermal: LD50 = > 3500 mg/kg; oral: ATE = 500 mg/kg			
12045-78-2	215-575-5	potassium tetraborate	0,125 - 0,25 %
	dermal: LD50 =	- > 2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately. Remove person to fresh air and keep comfortable for breathing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

The product is not: non-irritant.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Page 3 of 9

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Gases/vapours, toxic. Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Full protection suit

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Use personal protection equipment.

For emergency responders

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Provide adequate ventilation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Page 4 of 9

Store in a cool dry place. Provide adequate ventilation. Avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

In case of insufficient ventilation, wear suitable respiratory equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container.

Hints on joint storage

Do not store together with: Food and feedingstuffs

Further information on storage conditions

none

7.3. Specific end use(s)

Antifreeze agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL

8.2. Exposure controls





Appropriate engineering controls

See section 7. No additional measures necessary.

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and after work. Do not breathe vapour/aerosol. Separate storage of work clothes.

Eye/face protection

Wear eye/face protection.

Hand protection

Wear suitable gloves.

Suitable material: NBR (Nitrile rubber), PVA (Polyvinyl alcohol), CR (polychloroprene, chloroprene rubber), Butyl caoutchouc (butyl rubber)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

short-term: Filtering device (full mask or mouthpiece) with filter: A/P2 In case of major fire and large quantities: : Self-contained respirator (breathing apparatus)

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and c Physical state:	Liquid	
Colour:	various	
Odour:	characteristic	
Odour threshold:	not determined	
pH-Value:		7,5 - 8,5
Changes in the physical state		
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		not determined
Flash point:		111 °C
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Auto-ignition temperature:		> 400 °C
Decomposition temperature:		not determined
Vapour pressure:		not determined
Density (at 20 °C):		1,0641 g/cm³
Water solubility:		completely miscible
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:		not determined
Viscosity / kinematic:		not determined
Relative vapour density:		not determined
Solvent separation test:		Water: > 20 %
9.2. Other information		

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions. Keep away from heat.

10.3. Possibility of hazardous reactions

Reaction with: Acids, Alkali (lye), Oxidizing agent.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide Carbon dioxide Page 5 of 9

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Page 6 of 9

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1052,6 mg/kg

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
107-21-1	ethanediol, ethylene glycol					
	oral	ATE : mg/kg	500			
	dermal	LD50 : mg/kg	> 3500	Rabbit	Manufacturer	
12045-78-2	potassium tetraborate			-	-	-
	dermal	LD50 = mg/kg	> 2000	Rabbit	Manufacturer	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol, ethylene glycol) Organs affected: kidneys

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

none

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

Biodegradable.

12.3. Bioaccumulative potential

Based on the n-octanol/water partition coefficient accumulation in organisms is not expected.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Page 7 of 9

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Collect the waste separately. Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

List of Wastes Code - used product

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

14.6. Special precautions for user No information available.

Revision No: 2.00

No

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Page 8 of 9

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3	
2010/75/EU (VOC):	0 %
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water
Additional information	
Observe in addition any national regula	tions!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations** CAS: Chemical Abstracts Service M-Factor: Multiplication Factor DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) IMDG: International Maritime Code for Dangerous Goods **EmS: Emergency Schedules** MFAG: Medical First Aid Guide IATA: International Air Transport Association ICAO: International Civil Aviation Organization **TI: Technical Instructions**

according to UK REACH Regulation

JMC JM Uni coolant, ready to use

Revision date: 21.08.2023

Page 9 of 9

DGR: Dangerous Goods Regulations MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds EG or EC: European Community IE: Industrial Emissions SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to kidneys through prolonged or repeated exposure if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)